SNATCH BLOCKS BY GUNNEBO JOHNSON



Midget with Eye



1 Sheave with Hook



1 Sheave Tailboard

MIDGET—HOOK OR EYE

2 Ton capacity. 3.5 to 1 Design Factor. 3 inch diameter.

ONE SHEAVE—HOOK, SHACKLE, EYE OR TAILBOARD (no fitting)

3 through 30 ton capacities. 4 to 1 design factor. 4 through 24 inch diameters.

TOP DEADEND—HOOK OR SHACKLE

3 through 22 ton capacities. 4 to 1 design factor. 4 through 14 inch diameters.

TWO SHEAVE—HOOK OR SHACKLE

8 through 22 ton capacities. 4 to 1 design factor. 4 through 14 inch diameters.

2 Sheave with Shackle




Top Deadend with Hook

For Details Go to Our Website www.bairstow.com The Crosby Catalog Link or The Johnson Block Link

WAREHOUSE CROSBY SNATCH BLOCKS

STOCKED IN OUR











STOCKED IN OUR WAREHOUSE

418 STANDARD

CODE NO.	SHEAVE SIZE INCHES	SAFE WORKING LOAD* TONS	STANDARD WIRE ROPE INCHES	CENTER PIN DIAMETER INCHES	WEIGHT POUNDS EACH
108038	**3	2	3/8	3/4	3
108065	**4-1/2	4	1/2	1	11
108127	6	8	3/4	1-1/2	26
108225	8	8	3/4	1-1/2	33
108323	10	8	3/4	1-1/2	41
108421	12	8	3/4	1-1/2	48
108528	14	8	3/4	1-1/2	55
108608	16	12	7/8	2-1/2	130
108644	18	15	1	2-3/4	150

419 STANDARD

CODE NO.	SHEAVE SIZE INCHES	SAFE WORKING LOAD* TONS	STANDARD WIRE ROPE INCHES	CENTER PIN DIAMETER INCHES	WEIGHT POUNDS EACH
109037	**3	2	3/8	3/4	***3
109064	**4-1/2	4	1/2	1	12
109126	6	8	3/4	1-1/2	27
109224	8	8	3/4	1-1/2	34
109322	10	8	3/4	1-1/2	42
109420	12	8	3/4	1-1/2	49
109527	14	8	3/4	1-1/2	56
109607	16	12	7/8	2-1/2	135
109643	18	15	1	2-3/4	155

404 STANDARD

CODE NO.	SHEAVE SIZE INCHES	SAFE WORKING LOAD* TONS	STANDARD WIRE ROPE INCHES	CENTER PIN DIAMETER INCHES	WEIGHT POUNDS EACH
102016	**3	2	3/8	3/4	3
102025	**4-1/2	4	1/2	1	6
102098	6	8	3/4	1-1/2	15
102169	8	8	3/4	1-1/2	21
102230	10	8	3/4	1-1/2	29
102301	12	8	3/4	1-1/2	36