



## STANDARD LEVEL TYPE BINDER

Forged steel. Quenched and Tempered. Hooks are quenched and tempered alloy steel. Extra heavy construction at leverage point to prevent spreading. Heel of binder toggles away from load, permitting easy release. Ball and socket swivel joints at hook assemblies permit a straight line pull. L-150 available with links only; also snubbing type, releasing type and walking type binders.

CODE NO.	MIN.-MAX. CHAIN SIZE	WORKING LOAD LIMIT (LBS.)	TAKE UP INCHES	WEIGHT EACH
DL140	3/16 - 1/4	2600	3	2.5
DL380	5/16 - 3/8	5400	4.5	7.0
DL120	3/8 - 1/2	9200	4.5	11.2
DL580	1/2 - 5/8	13,000	4.75	19.2



## STANDARD RATCHET TYPE BINDER

Continuous take-up feature, infinite adjustment, gets the last half link of chain. One piece assembly, no bolts and nuts to loosen. Ratchet spring rust proofed. All load bearing or holding parts forged. Hooks are quenched and tempered alloy steel. Easy operating positive ratchet. Available without links and hooks.

CODE NO.	MIN.-MAX. CHAIN SIZE	WORKING LOAD LIMIT (LBS.)	TAKE UP INCHES	WEIGHT EACH
DR140	3/16 - 1/4	2600	8	3.5
DR380	5/16 - 3/8	6600	8	11.0
DR120	3/8 - 1/2	9200	8	13.7
DR580	1/2 - 5/8	13,000	8	14.6

NOTE: Special Ratchets up to 2" diameter and 165,000 lb. breaking strength available.