

WELDED CHAIN GRADE 100,80,70,30



G-100 ALLOY SLING CHAIN

Tested and rated for overhead lifting.

CODE NO. BLACK	CHAIN SIZE	WORKING LOAD LIMIT (LBS.)	DIA.	INSIDE WIDTH	INSIDE LENGTH	WEIGHT PER 100 FT. (LBS.)
140G100	1/4"	4,300	.28	.41	.83	77
380G100	3/8"	8,800	.40	.58	1.18	151
120G100	1/2"	15,000	.52	.72	1.54	253
580G100	5/8"	22,600	.63	.87	1.89	450
340G100	3/4"	35,300	.79	1.12	2.36	630

Larger Sizes or Grade 120 Available Upon Request



G-80 ALLOY SLING CHAIN

Tested and rated for overhead lifting.

CODE NO. BLACK	CHAIN SIZE	WORKING LOAD LIMIT (LBS.)	DIA.	INSIDE WIDTH	INSIDE LENGTH	WEIGHT PER 100 FT. (LBS.)
140G80	1/4"	3,500	.28	.39	.83	74
380G80	3/8"	7,100	.39	.55	1.2	151
120G80	1/2"	12,000	.51	.71	1.5	253
580G80	5/8"	18,100	.63	.87	1.9	382
340G80	3/4"	28,300	.75	1.0	2.2	524
780G80	7/8"	34,200	.87	1.2	2.6	738
100G80	1"	47,700	1.0	1.4	3.1	996
114G80	1-1/4"	72,300	1.26	1.7	3.8	1575



G-70 PREMIUM TIE DOWN CHAIN

Not for overhead lifting.

CODE NO. GOLD	CHAIN SIZE	WORKING LOAD LIMIT (LBS.)	DIA.	INSIDE WIDTH	INSIDE LENGTH	WEIGHT PER 100 FT. (LBS.)
140G70	1/4"	3,150	.281	.48	.84	74
516G70	5/16"	4,700	.327	.47	.99	100
380G70	3/8"	6,600	.406	.54	1.15	156
120G70	1/2"	11,300	.531	.73	1.45	259

NOTE: G-70 Transport Chain has a gold dichromate finish.



G-30 PROOF COIL GENERAL PURPOSE CHAIN

Not for overhead lifting.

CODE NO. BRIGHT	CODE NO. ZINC PLATED	CODE NO. HOT GALV.	CHAIN SIZE	WORKING LOAD LIMIT (LBS.)	DIA. (IN.)	INSIDE WIDTH (IN.)	INSIDE LENGTH (IN.)	WEIGHT PER 100 FT. (LBS.)
316S30	316Z30	316G30	3/16"	800	.218	.41	.96	38
140S30	140Z30	140G30	1/4"	1300	.276	.48	1.01	98
516S30	516Z30	516G30	5/16"	1900	.327	.50	1.11	144
380S30	380Z30	380G30	3/8"	2650	.390	.62	1.24	278
120S30	120Z30	120G30	1/2"	4500	.531	.82	1.51	422
580S30	580Z30	580G30	5/8"	6900	.656	1.01	1.88	628
340S30	340Z30	340G30	3/4"	10,600	.787	1.13	2.13	1069