



SHOCK ABSORBING LANYARDS WITH 3600 LB GATE HOOKS

STANDARD SHOCK ABSORBING LANYARDS




One inch wide nylon web lanyard with shock absorbing pack and double locking lanyard snap each end.

CODE NO.	LENGTH
Z901-3	3
Z901-4	4
Z901-6	6



One inch wide nylon web lanyard with shock absorbing pack and double locking lanyard snap one end. 1-3/4" throat ladder hook other end.

CODE NO.	LENGTH
Z902-3	3
Z902-4	4
Z902-6	6



One inch wide nylon web lanyard with shock absorbing pack and double locking lanyard snap one end. 2-1/4" throat rebar hook other end.


CODE NO.	LENGTH
Z903-3	3
Z903-4	4
Z904-6	6

100% TIE-OFF SHOCK ABSORBING LANYARDS




One inch wide 2-leg 100% tie-off lanyard with shock absorbing pack and three double locking lanyard snaps.

CODE NO.	LENGTH
ZY901-3	3
ZY901-4	4
ZY901-6	6



One inch wide 2-leg 100% tie-off lanyard with shock absorbing pack and double locking lanyard snap, plus two 1-3/4" throat ladder snaps.


CODE NO.	LENGTH
ZY902-3	3
ZY902-4	4
ZY902-6	6



One inch wide 2-leg 100% tie-off lanyard with shock absorbing pack and double locking lanyard snap, plus two 2-1/4" throat rebar snaps.


CODE NO.	LENGTH
ZY903-3	3
ZY903-4	4
ZY903-6	6

LOOP TYPE ATTACHMENT SHOCK ABSORBING LANYARDS




One inch web lanyard with shock absorber pack and attachment loop one end and lanyard snap other end. Loop is placed through back Dee ring, then the lanyard is fed through the loop to snug down for a secure attachment. Used where a lanyard snap is not desired.

CODE NO.	LENGTH
ZE901-3	3
ZE901-4	4
ZE901-6	6



One inch web lanyard with shock absorber pack and attachment loop one end and lanyard snap other end. Loop is placed through back Dee ring, then the lanyard is fed through the loop to snug down for a secure attachment. Used where a lanyard snap is not desired. 1-3/4" throat ladder hook.

CODE NO.	LENGTH
ZE902-3	3
ZE902-4	4
ZE902-6	6



One inch web lanyard with shock absorber pack and attachment loop one end and lanyard snap other end. Loop is placed through back Dee ring, then the lanyard is fed through the loop to snug down for a secure attachment. Used where a lanyard snap is not desired. 2-1/4" throat rebar hook.

CODE NO.	LENGTH
ZE903-3	3
ZE903-4	4
ZE903-6	6

ROPE TYPE SHOCK ABSORBING LANYARDS


1/2" nylon rope lanyards can also be supplied by using Code #'s Z701, Z702, Z703, or ZE701, ZE702, ZE703.

**SEE SAFETY INFORMATION
PAGES 145-147.**

NOTE: OTHER STYLES AND LENGTHS ARE AVAILABLE UPON REQUEST

SHOCK ABSORBING LANYARDS

TIE-BACK STYLE SHOCK ABSORBING LANYARD



One inch wide nylon web lanyard with shock absorbing pack and double locking lanyard snaps plus an adjustable tie-back ring.

CODE NO.	LENGTH
ZTB901-3	3
ZTB901-4	4
ZTB901-6	6

NOTE: Also available in ZTB902 with 1-3/4" throat ladder hook or ZTB903 with 2-1/4" throat rebar hook

STRETCH TYPE LANYARD WITH SHOCK ABSORBING PACK



Elastic Lanyard with a 4'-6' range. Keeps lanyard from tangling and out of the way.

CODE NO.	LENGTH
ZS901-6	6 ft. Extended, 4 ft. relaxed

Note: Other lengths and styles available



WEB ADJUSTERS

Available on all web lanyards. Can decrease length up to 50% of maximum.

REBAR CHAIN ASSEMBLIES (FOR POSITIONING ONLY)

MODEL 56



NO. 56S #11 REBAR CHAIN ASSEMBLY

1-3/4" throat opening, drop-forged steel, 5000 lb. test rebar snap hook. Two 5/8" throat double locking snap hooks. CAUTION: Do not use on attachments less than 1-1/4" diameter.

NO. 56G #18 REBAR CHAIN ASSEMBLY

Same construction as No. 56S except it incorporates a 2-1/4" throat rebar snap hook, which is compatible with the #18 rebar. CAUTION: Do not use on attachments less than 1-1/4" diameter.

MODEL 81



NO. 81S #11 REBAR CHAIN ASSEMBLY

Chain assembly eliminates the need for a swivel attachment. 1-3/4" throat opening, drop-forged steel, 5000 lb. test rebar snap hook. Two 5/8" throat opening double locking snap hooks. CAUTION: Do not use on attachments less than 1-1/4" diameter.

NO. 81G #18 REBAR CHAIN ASSEMBLY

Same construction as No. 81S except it incorporates a 2-1/4" throat rebar snap hook, which is compatible with the #18 rebar. CAUTION: Do not use on attachments less than 1-3/4" diameter.

MODEL 93



NO. 93S #11 REBAR CHAIN ASSEMBLY

1-3/4" throat opening, drop-forged steel rebar snap hook. Complete with swivel and Dee-ring. CAUTION: Do not use on attachments less than 1-1/4" diameter.

NO. 93G #18 REBAR CHAIN ASSEMBLY

Same construction as 93S except incorporates a 2-1/4" throat rebar snaphook, which is compatible with the #18 rebar. CAUTION: Do not use on attachments less than 1-3/4" diameter.

NOTE: Rebar chain assemblies are to be used as positioning devices only. A secondary approved lanyard must be used to prevent falls.