

G-411 STANDARD WIRE ROPE THIMBLES

Recommended for light duty service. Hot Dip galvanized steel. G-411 meets the performance requirements of Federal Specification FF-T-276b Type II, except for those provisions required of the contractor.

CODE NO.	ROPE DIA. (IN.)	WEIGHT PER 100 (LBS.)	DIMENSIONS (IN.)								
			A	B	C	D	E	F	G	H	
1037256	1/8	3.50	1.94	1.31	1.06	.69	.25	.16	.05	.13	
1037274	3/16	3.50	1.94	1.31	1.06	.69	.31	.22	.05	.13	
1037292	1/4	3.50	1.94	1.31	1.06	.69	.38	.28	.05	.13	
1037318	5/16	4.00	2.13	1.50	1.25	.81	.44	.34	.05	.13	
1037336	3/8	6.70	2.38	1.63	1.47	.94	.53	.41	.06	.16	
1037354	1/2	12.50	2.75	1.88	1.75	1.13	.69	.53	.08	.19	
1037372	5/8	34.50	3.50	2.25	2.38	1.38	.91	.66	.13	.34	
1037390	3/4	47.10	3.75	2.50	2.69	1.63	1.08	.78	.14	.34	
1037416	7/8	84.60	5.00	3.50	3.19	1.88	1.27	.94	.16	.44	
1037434	1	97.50	5.69	4.25	3.75	2.50	1.39	1.06	.16	.41	
1037452	1-1/8 - 1-1/4	175.00	6.25	4.50	4.31	2.75	1.75	1.31	.22	.50	

G-414 AND SS-414 EXTRA HEAVY WIRE ROPE THIMBLES

A rugged rope thimble recommended for heavy duty service. Available in Hot Dip galvanized or Stainless Steel. G-414 meets the performance requirements of Federal Specification FF-T-276b Type III, except for those provisions required of the contractor. SS-414 sizes available in stainless steel type 304.

G-414 GALV. CODE NO.	SS-414 STAINLESS CODE NO.	ROPE DIA. (IN.)	WEIGHT PER 100 (LBS.)	DIMENSIONS (IN.)								
				A	B	C	D	E	F	G	H	
1037639	1037960	1/4	6.50	2.19	1.63	1.50	.88	.41	.28	.06	.23	
1037657	1037988	5/16	11.80	2.50	1.88	1.81	1.06	.50	.34	.08	.28	
1037675	1038004	3/8	21.60	2.88	2.13	2.13	1.13	.63	.41	.11	.34	
1037693	—	7/16	34.70	3.25	2.38	2.38	1.25	.721	.47	.13	.38	
1037719	1038022	1/2	51.00	3.63	2.75	2.75	1.50	.81	.53	.14	.41	
1037737	—	9/16	51.00	3.63	2.75	2.69	1.50	.88	.59	.14	.41	
1037755	1038040	5/8	75.70	4.25	3.25	3.13	1.75	.97	.66	.16	.50	
1037773	1038068	3/4	158.10	5.00	3.75	3.81	2.00	1.22	.78	.22	.66	
1037791	—	7/8	177.80	5.50	4.25	4.25	2.25	1.38	.94	.22	.75	
1037817	—	1	313.90	6.13	4.50	4.94	2.50	1.56	1.06	.25	.88	
1037835	—	1-1/8 - 1-1/4	400.00	7.00	5.13	5.88	2.88	1.81	1.31	.25	1.13	
1037853	—	1-1/4 - 1-3/8	811.00	9.06	6.50	6.81	3.50	2.19	1.44	.38	1.13	
1037871	—	1-3/8 - 1-1/2	1294.80	9.00	6.25	7.13	3.50	2.56	1.56	.50	1.13	
1037899	—	1-5/8	1700.00	11.25	8.00	8.13	4.00	2.72	1.72	.50	1.38	
1037915	—	1-3/4	1775.00	12.19	9.00	8.50	4.50	2.84	1.84	.50	1.31	
1037933	—	1-7/8 - 2	2775.00	15.13	12.00	10.38	6.00	3.09	2.09	.50	1.50	
1037951	—	2-1/4	3950.00	17.13	14.00	11.88	7.00	3.63	2.38	.63	1.63	

