

CODE NO.	STD. PKG. QTY.	WEIGHT PER 100 (LBS.)	ROPE SIZE (IN.)	MINIMUM NO. OF CLIPS	AMOUNT OF ROPE TO TURN BACK IN INCHES	*TORQUE IN FT. LBS.
1010015	100	6	1/8	2	3-1/4	4.5
1010033	100	10	3/16	2	3-3/4	7.5
1010051	100	19	1/4	2	4-3/4	15
1010079	100	28	5/16	2	5-1/4	30
1010097	100	48	3/8	2	6-1/2	45
1010113	50	78	7/16	2	7	65
1010131	50	80	1/2	3	11-1/2	65
1010159	50	109	9/16	3	12	95
1010177	50	110	5/8	3	12	95
1010195	25	142	3/4	4	18	130
1010211	25	212	7/8	4	19	225
1010239	10	252	1	5	26	225
1010257	10	283	1-1/8	6	34	225
1010275	10	438	1-1/4	7	44	360
1010293	10	442	1-3/8	7	44	360
1010319	10	544	1-1/2	8	54	360
1010337	Bulk	704	1-5/8	8	58	430
1010355	Bulk	934	1-3/4	8	61	590
1010373	Bulk	1300	2	8	71	750
1010391	Bulk	1600	2-1/4	8	73	750
1010417	Bulk	1900	2-1/2	9	84	750
1010435•	Bulk	2300	2-3/4	10	100	750
1010453	Bulk	3100	3	10	106	1200
1010426•	Bulk	4000	3-1/2	12	149	1200

\*Electro-plated U-Bolt and Nuts • 2-3/4" and 3-1/2" base is made of cast steel. If a pulley (sheave) is used for turning back the wire rope, add one additional clip. If a greater number of clips are used than shown in the table, the amount of turnback should be increased proportionately.

\*The tightening torque values shown are based upon the threads being clean, dry, and free of lubrication.