

OVAL AND STOP SLEEVES

Sleeves for eye, lap, and stop sleeve splicing are available in either aluminum or copper in a wide variety of sizes ranging from 3/64" to 1/2" inclusive. All oval sleeves (copper or aluminum) are capable of supporting a load 40 to 60 percent of the rated breaking strength of the cable to which they are attached. Stop sleeves are capable of holding only 1/3 to 1/2 of the rated breaking strength of the cable to which they are attached if attached properly.

TO FIT CABLE DIAMETER	ALUMINUM OVAL	COPPER OVAL	ZINC PLATED COPPER OVAL	ALUMINUM STOP	COPPER STOP
3/64"	NICOA364	NICOC364	NICOZ364	STOPA364	STOPC364
1/16"	NICOA116	NICOC116	NICOZ116	STOPA116	STOPC116
3/32"	NICOA332	NICOC332	NICOZ332	STOPA332	STOPC332
1/8"	NICOA180	NICOC180	NICOZ180	STOPA180	STOPC180
5/32"	NICOA532	NICOC532	NICOZ532	STOPA532	STOPC532
3/16"	NICOA316	NICOC316	NICOZ316	STOPA316	STOPC316
7/32"	NICOA732	NICOC732	NICOZ732	STOPA732	STOPC732
1/4"	NICOA140	NICOC140	NICOZ140	STOPA140	STOPC140
9/32"	NICOA932	NICOC932	NICOZ932	STOPA932	—
5/16"	NICOA516	NICOC516	NICOZ516	STOPA516	—
3/8"	NICOA380	NICOC380	NICOZ380	STOPA380	—
7/16"	NICOA716	NICOC716	NICOZ716	—	—
1/2"	NICOA120	NICOC120	NICOZ120	—	—