## **INTERIOR VAN PRODUCTS**

## STANDARD LOGISTIC STRAPS



#### 651201 — 12'

2" Webbing with FE8306-1 Spring Fitting, Code 01. Cam Buckle 43010, Webbing 4900, Track Type Series E,A. Assembly Breaking Strength 2,500 lbs. Working Load Limit 835 lbs.

#### 651601 — 16'

2" Webbing with FE8306-1 Spring Fitting, Code 01. Cam Buckle 43010, Webbing 4900, Track Type Series E,A. Assembly Breaking Strength 2,500 lbs. Working Load Limit 835 lbs.

#### 641201 — 12<sup>'</sup>

2" Webbing with FE8306-1 Spring Fitting, Code 01. Ratchet Buckle 811, Webbing 4900, Track Type Series E,A. Assembly Breaking Strength 3,000 lbs. Working Load Limit 1,000 lbs.

#### 641601 — 16<sup>°</sup>

2" Webbing with FE8306-1 Spring Fitting, Code 01. Ratchet Buckle 811, Webbing 4900, Track Type Series E,A. Assembly Breaking Strength 3,000 lbs. Working Load Limit 1,000 lbs.

#### 841211 - 12', 831611 - 16' and 832011 - 20'

1-3/4" Webbing with FE8029-1 Spring Fitting, Code 11. Overcenter Buckle FE7707-1, Webbing FE102G, Track Type Series E,A. Assembly Breaking Strength 4,000 lbs. Working Load Limit 1,335 lbs.

### LOGISTIC TRACK





# 11111111111





#### 43002 SERIES E TRACK HORIZONTAL

High strength steel, 12 gauge. 50,000 psi minimum yield. Iron phosphate, green primer finish. Weight: 16.6 lbs./7.5 kgs. Length: 10 ft./3m.

#### 2007 SERIES A TRACK HORIZONTAL

High strength steel, 12 gauge. 50,000 psi minimum yield. Iron phosphate, green primer finish. Weight: 16.6 lbs./7.5 kgs. Length: 10 ft./3m.

#### FE725-01 ALUMINUM SERIES A TRACK HORIZONTAL

Aluminum. 37,000 psi minimum yield. Natural finish. Weight: 8.3 lbs./3.8 kgs. Length: 10 ft./3m.

#### 2005 SERIES F TRACK HORIZONTAL OR VERTICAL

High strength steel, 15 gauge. Galvanized finish. Weight: 6.9 lbs./3.1 kgs. Length: 10 ft./3m.

#### 2019 SERIES E TRACK VERTICAL

High strength steel, 11 gauge. 50,000 psi minimum yield. Iron phosphate, green primer finish. Weight: 11.6 lbs./5.3 kgs. Length: 10 ft./3m.

#### FE720-01 SERIES A TRACK VERTICAL

High strength steel, 11 gauge. 50,000 psi minimum yield. Iron phosphate, green primer finish. Weight: 13.2 lbs./6.0 kgs. Length: 10 ft./3m.

All ratings for Series E or A fittings are based on using 43002 or FE702-01 track. Rating may be reduced when fittings are used in other tracks.

# 

## **OTHER LOGISTIC STRAP HARDWARE**



1831

F-Track



Wire Hook





FE8264-1 Series E/A Fitting with 1" Round Ring. 6000 lbs. Breaking Strength. 2000 lbs. WLL.



FE8029-1 Series E/A Spring Loaded Fitting. 4500 lbs. Breaking Strength. 1500 lbs. WLL

BAIRSTOW LIFTING PRODUCTS CO. • 1-800-241-8990 • SHOP ONLINE www.bairstow.com