



## COLD SHUTS—NO. 1 PLAIN

Size	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4
Code No. Self Colored	D50090	D50190	D40290	D50390	D50490	D50590	D50690	51790
Code No. Zinc Plated	D50091	D50191	D50291	D50391	D50491	D50591	D50691	51791
Weight per 100 lbs.	3	6	10	18	26	38	78	128

Applications: As temporary repair link, use one size larger than G-30 chain with which it is to be used. Not for Lifting or Tie Down use.



## CONNECTING LINKS

Size	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Code No. Clear Finish	M613	M614	M615	M616	M617	M618	M620	M622	M624	M626
Code No. Electro Galv.	M613G	M614G	M615G	M616G	M617G	M618G	M620G	M622G	M624G	M626G
Rated Working Load (lbs.)	800	1,300	1,900	2,650	3,500	4,500	6,900	9,750	12,800	14,000
Weight per 100 lbs.	3	8	12	20	29	42	75	116	175	240

For use on G-30 chain only. Not for Lifting or Tie Down Use.



## REPAIR LINKS / LAP LINK

BRIGHT CODE NO.	ZINC PLATED CODE NO.	Size	QTY. PER CARTON	WEIGHT PER 100 (LBS.)
—	653612	1/8 x 3/4	100	3-1/8
653180	653618	3/16 x 1	100	3-1/4
653211	653621	7/32 x 1-1/4	50	4-3/4
653251	653625	1/4 x 1-1/4	50	6-3/4
653253	653626	1/4 x 1-1/2	50	7-1/4
653255	653627	1/4 x 2	50	9-2/4
653281	653628	9/32 x 1-1/4	50	8-1/4
653312	653631	5/16 x 1-1/2	50	13
653315	653632	5/16 x 2	50	17
653373	653633	3/8 x 1-5/8	50	23
653375	653638	3/8 x 2	50	26
653506	653650	1/2 x 2-1/2	25	53

Applications: A temporary repair link for light applications. Not for Lifting or Tie Down use.




FIG. 1


FIG. 2

## “S” HOOKS


BRIGHT CODE NO.	ZINC PLATED CODE NO.	NO.	MATERIAL SIZE	INSIDE LENGTH (IN.)	WEIGHT PER 100 (LBS.)
687120	687420	20	.080	27/32	5/16
687121	687421	21	.080	11/16	1/4
687140	687440	40	.134	1-1/16	1
687160	687460	60	.192	1-13/16	3-1/2
687161	687461	61	.204	1-5/8	3-7/8
687162	687462	62*	.175	1-3/8	2-1/2
687172	687472	72*	.225	1-1/2	4-3/4
687180	687480	80	.250	1-13/16	6-1/2
687181	687481	81	.250	2-1/2	8
—	687484	84*	.250	1-25/32	6-1/4
687190	687490	100	.312	2-1/4	11-3/4
687192	687492	120	.375	2-3/8	19-1/2

Packed 50 pieces per carton. \*See Figure 2 for these sizes only.

Applications: Used to attach accessories to chain. Light duty only. Not for Lifting or Tie Down use.



NO. 2450



NO. 2451

### NO. 2450 SPRING HOOKS Plated formed steel

Diameter	3/16	1/4	5/16	3/8	7/16	1/2	1/2
Length Overall	2-1/8	2-1/2	3-1/8	4	4-3/4	5-1/2	6-3/8
Snap opening	1/4	5/16	3/8	1/2	5/8	3/4	1
Working Load Lt.	100	140	280	400	500	600	700
Wgt. per 100	4	7	15	30	43	60	80

### NO. 2451 SPRING HOOKS with RINGED EYE Plated formed steel

Diameter	3/16	1/4	5/16	3/8	7/16	1/2	1/2
Length Overall	2-1/8	2-1/2	3-1/8	4	4-3/4	5-1/2	6-3/8
Snap opening	1/4	5/16	3/8	1/2	5/8	3/4	1
Working Load Lt.	100	140	280	400	500	600	700
Wgt. per 100	4	7	15	30	43	60	80