

DOUBLE BRAIDED ROPES

Double braids are actually two ropes in one. The jacket is braided over a braided core. Braid on Braids are very flexible and have a high strength to weight ratio. The jacket also serves to protect the core. Braid on braids remain round and firm and will not rotate under load. They are spliceable. Sizes from 1/4" to 1-5/8" diameter.

POLYESTER DOUBLE BRAID

is constructed of a polyester cover and core. This braid provides high strength with low stretch and excellent abrasion resistance. Applications: mooring lines, stringing lines, winch lines, underground pulling lines, guy lines, slings, bull ropes.

CODE NO.	DIA.	CIRCUM.	WEIGHT LBS./100 FT.	AV. TENSILE STRENGTH
PB140	1/4"	3/4"	2.5	2,800
PB516	5/16"	1"	3.6	4,200
PB380	3/8"	1-1/8"	5.0	5,550
PB716	7/16"	1-1/4"	6.4	7,400
PB120	1/2"	1-1/2"	8.9	9,900
PB916	9/16"	1-3/4"	11.6	12,600
PB580	5/8"	2"	14.2	15,600
PB340	3/4"	2-1/4"	18.0	19,600

CODE NO.	DIA.	CIRCUM.	WEIGHT LBS./100 FT.	AV. TENSILE STRENGTH
PB780	7/8"	2-3/4"	27.0	29,000
PB100	1"	3"	36.8	37,500
PB118	1-1/8"	3-1/2"	45.0	46,000
PB114	1-1/4"	3-3/4"	54.0	54,500
PB1516	1-5/16"	4"	61.0	61,500
PB112	1-1/2"	4-1/2"	73.0	71,500
PB158	1-5/8"	5"	86.0	87,200

600 ft. standard reel. See Page 128 for working load information.

NYLON DOUBLE BRAID

is constructed of a nylon cover and core. This braid provides high strength as well as excellent shock absorbing elasticity. Applications: mooring lines, towing lines, anchor lines.

CODE NO.	DIA.	CIRCUM.	WEIGHT LBS./100 FT.	AV. TENSILE STRENGTH
NB140	1/4"	3/4"	1.7	2,330
NB516	5/16"	1"	2.6	3,400
NB380	3/8"	1-1/8"	3.7	4,800
NB716	7/16"	1-1/4"	5.0	6,600
NB120	1/2"	1-1/2"	6.4	8,300
NB916	9/16"	1-3/4"	8.4	11,800
NB580	5/8"	2"	12.0	14,700
NB340	3/4"	2-1/4"	16.0	20,000

CODE NO.	DIA.	CIRCUM.	WEIGHT LBS./100 FT.	AV. TENSILE STRENGTH
NB780	7/8"	2-3/4"	21.8	27,400
NB100	1"	3"	26.0	33,000
NB118	1-1/8"	3-1/2"	35.8	44,000
NB114	1-1/4"	3-3/4"	41.0	50,600
NB1516	1-5/16"	4"	46.8	57,400
NB112	1-1/2"	4-1/2"	59.8	72,000
NB158	1-5/8"	5"	74.0	88,200

600 ft. standard reel. See Page 128 for working load information.

TRICK LINE (BLACK THEATRICAL ROPE)

Black cotton jacked rope used in stage rigging.

CODE NO.	SIZE	BREAKING STRENGTH	SPOOL LENGTH	WT./100' LBS.
TR1806	1/8"	99 lbs.	600'	.3
TR18025	1/8"	99 lbs.	2500'	.3
TR18030	1/8"	99 lbs.	3000'	.3

OTHER STYLES, SIZES, COLORS AND LENGTHS AVAILABLE

WHITE SOLID BRAID NYLON ROPE

icals, and with shock-absorbing elasticity that allows it to withstand great strain. Solid braided construction. stays round and works well in pulleys. Natural silvery white color. Working loads are derived by taking 15-20% of approx. avg. new rope tensile strength.

CODE NO.	SIZE NO.	DIA. (IN.)	REC. WORK LOAD (LBS.)	UNIT	WT. (LBS.)
SB18010	4	1/8	69	1000 FT. SPOOL	5
SB31610	6	3/16	135	1000 FT. SPOOL	12
SB14010	8	1/4	169	1000 FT. SPOOL	17
SB3805	12	3/8	450	500 FT. SPOOL	19
SB1205	16	1/2	714	500 FT. SPOOL	16

NOTE: Other spool lengths are available