

# WOOD SHELL BLOCKS WITH STEEL FRAME

BLOCK SIZE (IN.)	FITTING	SINGLE SHEAVE			DOUBLE SHEAVE			TRIPLE SHEAVE	
		21 C STOCK NO. GALV.	21 B STOCK NO. GALV.	21 R STOCK NO. GALV.	22 C STOCK NO. GALV.	22 B STOCK NO. GALV.	22 R STOCK NO. GALV.	23 B STOCK NO. GALV.	23 R STOCK NO. GALV.
3	HS	602217	603813	603617	602618	604616	604411	605410	—
4	HS	602235	603831	603635	602636	604634	604439	605438	605232
5	HS	602253	603859	603653	602654	604652	604457	605456	—
6	HS	602271	603877	603671	602672	604670	604475	605474	605278
8	HS	602315	603911	603715	602716	604714	—	605517	605312
3	N	—	606419	—	—	606810	—	607212	—
4	N	—	606437	606231	—	606838	606632	607230	607034
5	N	—	606455	—	—	606856	606650	607258	—
6	N	—	606473	—	—	606874	606678	607276	607070
8	N	—	606516	—	—	606918	—	607310	—
3	S	—	610011	—	—	611617	—	613214	—
4	S	—	610039	—	—	611635	—	613232	—
5	S	—	610057	—	—	611653	—	613250	—
6	S	—	610075	—	—	611671	611476	613278	—
8	S	—	610119	—	—	611715	611519	613312	—

Bearing Code: C - Common, R - Roller, B - Bronze Self Lubricating.

BLOCK SIZE (IN.)	SHEAVE DIAMETER (IN.)				MANILA ROPE SIZE (IN.)	WORKING LOAD LIMIT* (LBS.)			WEIGHT EACH (LBS.)		
	OUTSIDE DIAM.	RIM THICKNESS	CENTER PIN DIAM.			21 SINGLE	22 DOUBLE	23 TRIPLE	21 SINGLE	22 DOUBLE	23 TRIPLE
3	1.75	.50	.38		3/8	500	800	1200	1.00	1.75	2.50
4	2.25	.63	.38		1/2	1000	1400	1800	1.75	3.00	4.00
5	3.00	.75	.38		5/8	1200	1800	2400	3.25	5.60	6.50
6	3.50	1.00	.50		3/4	1800	2500	3200	5.00	8.50	11.50
8	4.75	1.13	.63		7/8 - 1	2800	3800	4800	9.00	14.00	21.50

\*Ultimate Load is 4 times the Working Load Limit.

NOTE: We furnish beackets on all blocks. For Reeving information, see page 107.